

Energy-saving two- and three-way electric valve (Three-wire type)

New generation of energy-saving products
Low power consumption, only when the valve position needs to be changed.

- Working power : 220V AC , 50Hz
- Ambient temperature : 0~65℃ max
- Power consumption : 4AV
(When the valve changes position)
- Fluid temperature : 1~95℃
- Time (standard value) : Valve opens : 7s 50Hz
- Differential pressure when closed : 400KPa
- Stress amount : Static pressure : 2067KPa ;
Impact pressure 10MPa



Two-way valve	
3/4"	TC2P-01
1"	TC2P-02
Three-way valve	
3/4"	TC3P-01
1"	TC3P-02

- Double spring design, never break.
- Low voltage can be started, special institutions use super strong American UL, CSA long-life motor(MAMS)
- Aluminum alloy motor room, all metal fireproof (non-plastic products)
- Large ball room opening and closing stroke, long no water hammer.
- Exclusive cooling mechanism.

Feature of product

1. Double spring design, never break
2. Low voltage can be started, special institutions use super strong American UL , CSA Long Life Motor (MAMS)
3. Aluminum alloy motor room, all metal fireproof (non-plastic products)
4. Large ball room opening and closing stroke, long no water hammer.
5. Exclusive cooling mechanism, the motor does not freeze, rust or stuck.



World famous brand all kinds of two and three way valve motor
Electro, Synchnorous, Hansen <Taiwan distributor>
Welcome OEM wholesale, Special for retail, repair, replacement
and new installation.