

T-486 Thermostat Series



Dimensions : 130 x 90 x 20 mm
Horizontal and Vertical Dimensions

1. Easy to operate

Number display : actual room temperature, set temperature, timer.
LED lights indicate : Wind strength, timer setting, automatic setting.

2. Highly Accurate Temperature Control

Temperature setting range : 16°C~32°C

3. Multi-Function Thermostat

- On/Off preset setting 1~12hrs.
- Applicable for split and direct-expansion systems with 3 minute protection.
- Can be attached to the Chilled-Water remote signal control.

4. Easy to Install : 3 Wires

- Applicable for any brands of air conditioners.
- Unit Controller is installed on the FCU.
- One to many FCU This thermostat can control many FCU systems.

T-486 Control Unit

3 Wires and Sensor



Horizontal(H) and vertical(V) 110V(A) 220V(B)

| Model | Cooling Only | Heat / Cooling | Wind Strength | | R-allows chiller controls | Timer Function | 3 minutes protection for direct expansion system | Applications |
|---------|--------------|----------------|---------------|-----------|---------------------------|----------------|--|--|
| | | | Manual | Automatic | | | | |
| T-486-1 | √ | | √ | √ | √ | √ | | Central Chilled water system (cooling only) |
| T-486-2 | | √ | √ | √ | √ | √ | | Central Chilled water system (cooling / heating) |
| T-486-3 | √ | | √ | √ | | √ | √ | Direct Expansion (for use with contactor) |
| T-486-4 | √ | | √ | √ | | √ | √ | Large current25A Split systems |



Since1991
Design and manufacture
/ Made in Taiwan

CANNEX TECHNOLOGY INC.

<http://www.akr.com.tw>
Tel : +886-4-861-3883(Rep) Fax : +886-4882-8209
Add : No.182, Sec.2, Yuanlu Rd., Sihu, Changhua, 51449, Taiwan

